THE CITY OF PALM COAST CDBG HOUSING REHABILITATION PROGRAM WORK WRITE-UP/BID FORM

OWNER: Wanda Connelly

ADDRESS: 39 Slipper Orchid Trail E. Palm Coast, FL 32164

PHONE #: 386-586-7735

DATE: February 27, 2015

Home Built in 2000.

- Lead Base Paint Actions Do Not Apply: \geq
- ACM Actions **Do Not** Apply: \triangleright
- Mold Actions Do Not Apply

Take Notice of any attachment pertaining to any Regulated Asbestos Containing Material (RACM), Lead Based Paint (LBP) or Mold and follow all recommended actions for remediation, prevention and/or Disposal. If there are not attachments pertaining to RACM, LBP, or Mold it is reasonable to assume that no actions are required.

Note	System	Description of Work	Location	Price	Contractor Initials
Α.	REHABILITATION	Special attention should be directed to the attached reports regarding Lead Base Paint, Asbestos, and/or Mold. Any recommendations included in the reports regarding such material shall become part of the Work.	Unit	N/A	
В.	SITEWORK	Rehabilitation of unit shall include: 1. Re- connects all existing TV, Satellite connections, & Phone Jacks. Install 911 addressing as required. 2. Disconnect and re-connect to community water/sewer systems if required by code or specification within this document. 3. Demolition and safe, legal, disposal of all materials, removal of all construction and replacement debris. 4. Disconnect and re-connect existing system or to community water/sewer systems (where applicable).	All	INCLUDED IN BID	

THIS PAGE MUST BE INCLUDED WITH THE BID FOR IT TO BE VALID

All work to be performed in a workmanlike manner, in accordance with the CDBG Program Specifications as listed in this Scope of Work, Florida Building Code, and manufacturer's specifications. The contractor shall be responsible for the repairs and/or reinstallation of materials/equipment/fixtures damaged or removed due to any work item contained herein. Contractors shall properly dispose of all fixtures, materials and other items removed from the dwelling unless otherwise specified herein. Bid will be accepted on the TOTAL BID submitted, and all items must be cost itemized in the space provided or the bid will be rejected.

This house may or may not require the homeowner to vacate the premises during the construction period. In the case of the CDBG program unit will be vacant and shall remain so for the duration of the rehabilitation and construction process.

This document may not be altered in any manner. The scope of work set forth in this document may not be changed without the written consent of Guardian CRM, Inc. under direct authorization from the City of Palm Coast and/or its official representatives.

I hereby certify that I am licensed by the State of Florida, Department of Business and Professional Regulation, and that I am eligible to participate in the CDBG Housing rehab Program. I also agree that change orders above the original contract amount shall only be paid for with CDBG funds to correct documented code violations or to meet Section 8 Housing Quality Standards. Change orders must be approved by the homeowner or his/her representative, the contractor, and local government prior to any initiation of work based on that change order.

Company Name (Print Name): Contractor Name (Print Name):

Contractor's Address:

Contractor's Phone Number:

_____Contractor's Email:_____

1

EXHIBIT "A" - SCOPE OF WORK

(Work Listed Below)

NOTICE TO BIDDING GENERAL CONTRACTORS

1) All bids to include the repair/repaint to match existing, all damaged (plaster, stucco, Tile, or any other material), walls, ceilings, ECT... affected by construction.

2) All bids are subject to "or equal" in quality and/or value line item substitutions. Or equal substitutions where the line item is not being changed can be approved by the Inspector or housing coordinator verbally. Where line items are being altered the "or equal" substitution must be documented in writing.

3) No work shall begin until all permits are pulled and submitted to the City. Starting work prior to obtaining permits will result in a 1 round suspension, and second violation will result in a full year program suspension, and third violation will lead to suspension not to exceed 3 years.

4) A list of all subcontractors must be submitted with this bid. The subcontractor list must be amended if or when it changes during the progress on of any housing rehab activities.

Failure to provide any required notifications will result in a violation of the terms and conditions of the SOW and Work Rehabilitation Contract and a loss of payment on the substituted product if it is not replaced with the SOW specified product. Approval will <u>NOT</u> be granted under any circumstance on or after the fact basis.

NOTE: Signature required for acknowledgment of Notice to Bidding General Contractors.

Printed Name	Signature	Date
1. General Construction and Operational:		
1a. General Construction and Operational:		

0	To include all applicable Plans, Fees, and Permitting	\$

2. Exterior Rehabilitation:

2a. Roof Covering

INTRO: All roofing work shall be completed by a legal and appropriately licensed roofing firm. At the conclusion of any work the roofing company must provide an affidavit stating that the work was completed to all specification and/or code requirements and provide notice that the units roofing system is in safe and code compliant working order. The Contractor understands that failure to provide this affidavit may result in nonpayment of this item and agrees that the owner, the City, and any of its agents will not be held liable due to contractor negligence in providing all required documentation needed for payment.

Removing all existing roofing shingles and covering (primary unit/garage) including all deteriorated material: Install two (2) layers of ASTM 30lb felt paper, and new, 30 year asphalt, dimensional, architectural, fungi resistant, self sealing shingles. Replace sheathing and/or decking, and rafter/trusses top chords (15%) or as required, any percentage above fifteen (15) will require an approved additional material change order. Replace all vents with code compliant products and material per the shingle manufacturer's specifications over all roof ridge(s).

Connect roof sheathing to the roof framing with eight-penny weight ring shank nails in accordance with code compliant spacing. Use wood adhesive underneath the sheathing along the connecting joint with the roof trusses where applicable. Installation to include new 2"x 2" metal drip edge (with 1/4inch offset from fascia) and flashing shall be installed throughout the entire roof system.

One 36" layer of self adhering modified underlayment shall be placed above flashing in all valleys. The entire new roof system shall conform to building code of jurisdiction Homeowner must be given a minimum of three color/style selection choices; <u>No</u> <u>fasteners shall penetrate into the fascia or 1x2 wood drip edge nailer</u>; (5 year warranty required). (Recommended Product: Tamko Algae resistant or equal in value and quality)

Note 1: Roof covering repairs shall include the inspection and proper sealing of all existing skylight (approx 4 units).

Note 2: Where existing gutters are required to be removed to allow for roofing replacement, the condition of each section to be removed and reinstalled shall be documented <u>IN WRITING</u> with the homeowner. Reinstallation should meet or exceed the documented operational order as applicable.

Note 3: This SOW does not include any work for Fascia and/or Soffit. Any work required for these components shall be documented with an inspection report and list any repairs/replacement material, and labor costs required to repair/replace the deteriorated or improper items; If approved the items will be addressed via change order.

Note 4: Owner shall have choice of shingle color

0

Roof Repairs (As listed)______\$____

2b. Windows:

Remove <u>7</u> existing windows (Front-3; Right-0; Rear-3; Left-1). Replace windows with new dual pane, single hung Energy star rated windows with aluminum framed screen. Bathrooms shall have obscure glass. Replace existing with marble sill(s). Provide Modifications to openings and electric if necessary to accommodate the new windows. <u>Windows must be energy star rated for the Southern Region (Florida) of the United States (Recommended Product: PGT WinGuard or equal in value and quality)</u>

Note 1: Contractor shall submit all product approvals, stamped by the Building Department of jurisdiction, with this Project's closeout package.

Note 2 Patch holes and touch up the paint patches and discolored finish resulting from the removal of existing window(s) to match existing as close as possible. Inspector shall be responsible for determining if the touch-up paint matches as close as possible. ALL PARTIES there is a high probability that there will be a slight to moderate difference in the color of the touch up paint versus the existing paint. This is common where existing surfaces are being

Note 3: All window installation shall include any required drywall repairs due to moisture damage and any damaged caused by window installation. Repairs shall be painted in accordance with the existing color scheme and finish.

Note 4: Any existing window, shutters, shade awnings or security bars that interfere with the installation of windows, shall be inspected for material and component condition, and tested for working or operational condition. The condition and operational status of each shall be recorded and presented to the owner for signature and to the inspector for records purposes.

All removed shutters, awnings or security bars shall be stored in an owner appointed location on site, and reinstalled (where code allows or a written exception is granted by the City Building department) in their existing footprint and be tested for operational order and be tested, recorded and presented to the owner for signature and to the inspector for records purposes. Any awnings or security bars that do not interfere with window installation shall not be touched.

0	Windows (As listed)	\$

2c. Exterior Door:

Remove the existing front primary/entry/exit door and jambs, prepare a sufficient door buck, and install pre-hung metal clad energy star rated door in the footprint of the previously removed door (including glazed panel)-to match existing swing (Recommended Entry/Exit Doors Product NOA#-PGT Windows and Doors or equal in value and quality).

Install new interior wood casing and exterior covering as required: Prepare new door assembly for painting by washing with TSP and light sanding then apply one (1) coat of acrylic primer/sealer and two (2) coats of acrylic semi-gloss paint to match existing finishes: Homeowner must be given a minimum of three color/style selection choices

Door installation shall include keyed (alike) entry lockset with lever handle (both sides): "Schlage", Flair F51 and matching deadbolt or approved equal, deadbolt keyed one side to the lock set peephole, vinyl bubble weather-stripping, wind crash chain stop, and aluminum threshold.

Note 1: Door paint color choice shall be by owner in accordance with HOA/deed restrictions, homeowners association, and building code of jurisdiction. Contractor shall comply with manufacturer recommend time intervals between coats of paint and shall deliver smooth full paint coverage. Roller and brush marks, runs, orange peels, and other defective paint application shall not be accepted.

Note 2: Any repairs and touch up paint required to areas affected by construction are to be included in this line item.

Front Entry/Exit Door (1- ½ light unit with internal blinds)

3. General Interior Rehabilitation

3a. Interior Flooring:

Remove all floor covering in the listed areas and replace with new 10mm wood laminate floor covering with attached premium under-padding. Laminate product should contain SureLock technology, PermaMax wear layer, and Scratch Guard to limit wearing, scuffing, and scratching. Installation to be complete and include all required components, to ensure installation to manufacturers specifications. *Exact dimensions and square footage to be determined by contracting firm.* (Recommended carpet product: Pergo XP or equal in quality and value)

0	Interior Flooring Replacement (Living Room)	\$
0	Interior Flooring Replacement (Dining Room)	\$
0	Interior Flooring Replacement (Master BR)	\$
0	Interior Flooring Replacement (BR #2)	\$
0	Interior Flooring Replacement (BR #3)	\$

3b. Master Bathroom:

- Remove existing and Install a new white, elongated, comfort height/handicapped (18"), maximum 1.6 gallon per flush toilet, including all required (new) hardware and components, values, seal rings, connectors, to ensure complete installation and operational order in the following locations: Master Bathroom and Bathroom #2: Recommended product: American Standard or equal in quality and value)
 - Toilets (1 units) ______\$______

4. HVAC/Electrical

4a. HVAC:

Remove existing and install new minimum 2.5 ton (or as required per energy calcs) 14 SEER split central heating and air conditioning system with electric heat pump (strip sized to accommodate the housing unit's living space). Rheem Prestige Series or approved equal in value and quality.

The system is to include service to all habitable rooms, including cleaning all existing ducts/plenums: the complete system shall include : compressor air handler, piping ,Electrical service connects/disconnects, programmable thermostat and all other components necessary for a complete working system; Exterior compressor must be installed (where none exists) on a minimum 3X3 concrete pad and bolted to the pad.

Note 1: Contractor shall provide drawings, energy calculations, and documents as required to perform the scope of work.

HVAC All habitable rooms (Approx 1 complete unit)_____\$_____\$______

5a. Septic: (Inspection Only)

Inspect the units septic/sewage system/connections. Inspection to ensure all required materials (take note of any lift/pump mechanisms) and components to ensure proper installation to meet all required federal, state, and local codes, including Flagler County Health Department requirements. A 3rd party report showing the findings at the time of inspection will be provided to the Project Manager before any payment is made or change orders will be granted.

NOTE 1: All septic/plumbing work shall be completed by a legal and appropriately licensed firm. The septic/plumbing company shall conduct a review of the newly installed system and provide an affidavit stating that the work was completed and provide report on the condition of the unit's septic system. Any found deficiencies found by the septic/plumbing contractor shall be provided to the GC listing any additional repairs needed above what is listed in the SOW. The Contractor understands that failure to provide this affidavit and report may result in nonpayment of this item and agrees that the owner, the City, and any of its agents will not be held liable due to contractor negligence in providing all required documentation needed for payment.

NOTE 2: Sod replacement for all disturbed areas shall be included in the bid.

0	Septic (Inspection)	\$

-END SOW-

EXISTING DWELLING FOOTPRINT





- EXISTING DWELLING FOOTPRINT

TOTAL bid for 39 Slipper Orchid------→ \$____

Special Notes

Any and all products or services included in this scope of work shall be installed to the manufactures specifications and in compliance with all applicable Health Department, NEC, UPC, and/or Florida Building Codes.

All NOA product numbers can be found at <u>www.miamidade.gov/buildingcode/pc-search_app.asp.</u> All products with no NOA # number can be found at. <u>www.homedepot.com</u>, <u>www.lowes.com</u>, or other retail outlets where such products are sold.

HOMEOWNER SIGNATURE:	DATE:
CO-OWNER SIGNATURE:	DATE:

CONTRACTOR Printed Name:		PHONE:
CONTRACTOR Signature:		DATE:
	OFFICIAL USE ONLY	
DATE SUBMITTED:	DATE ACCEPTED:	
BID OPENED BY:	WITNESSED BY:	
DATE OPENED:	TIME:	
WORK WRITE-UP PREPARED BY:	Antonio Jenkins	Date: February 2015